


 Via S.S. Grisante e Daria, 70 – 42124 Reggio Emilia (RE) - ITALY tel +0039 0522/518703 fax + 0039 0522/277963 www.electroil.it		Symbol	Meas. Unit	ITTP2,2W-BC  
GENERAL DATA	Maximum motor-pump power	P_{2n}	kw Hp	2,2 3,0
	Inverter voltage supply	V_1	V	3x(200-440)V
	Frequency supply Inverter	f_1	Hz	50-60
	Inverter Voltage output	V_2	V	3x(200-440)V
	Inverter Frequency output	f_2	Hz	0..55
	Maximum output current (ED 100%)	I_2	A	4
WORKING CONDITIONS	Nominal input current	I_{1n}	A	5
	Maximum output current (<1 sec.)	I_2	A	$2.5 \times I_2$
	Pressure measure range	ΔP	Bar	0 – 10
	Pressure transducers compatibles			In: 0-15V Out: 4-20 mA
CHARACTERISTICS	Mounting type			Wall fixing
	Control type			V/f
	User interface			Display 2x16
	Communication with others Inverters			 Bluetooth
	Cooling type			Forced convection
	Protection grade			IP54
	Dimensions	b h p	mm	155x238 x120
	Weight		kg	3,0

For every inverter:

- 1) included a pressur trasducer K16
- 2) storage temperature from -20°C to +60°C
- 3) ambient temperature from 0°C to +40°C