

Jebao - ECO-A PUMP

Series FTP4600, 6500, 8500, 10000 12000, 15000 and 20000 LPH

Filter & Waterfall Pond Pumps

The Jebao FTP Series of pumps are submersible, fitted with low energy, high performance asynchronous motors with high pump heads and flow rates. The pumps are fitted with long life ceramic shafts and have 10 metres of 3 core electric cable. The pumps are designed to pump solids up to 6mm in diameter with minimal pre-strainer maintenance.

Model	Watts	Q.max.(L/H)	H max.(m)	Dimensions L*W*H
FTP4600	35	4500	2.6	292*290*158mm
FTP6500	65	6500	3.7	292*290*158mm
FTP8500	95	8500	4.5	292*290*158mm
FTP10000	115	10000	5.0	292*290*158mm
FTP12000	130	12000	5.5	340*337*173mm
FTP15000	180	15000	6.0	340*337*173mm
FTP20000	220	20000	6.2	340*337*173mm

ATTENTION: From the 1st January 2005 installing this product in the garden is classed as 'notifiable' in the Building Regulations for England and Wales. The Regulations now require you to inform your local authority building control department that you intend to install this product prior to installation. They will advise you as to how you can get your installation approved.

WARNING: SAFETY & ELECTRICAL CONNECTIONS. These pumps are designed to be permanently wired to the mains supply in a dry weatherproof enclosure through a Double-Pole Switched Fused Spur conforming to BS3676, fitted with a 3 or 5 Amp fuse. The installation must conform to the National and Local wiring regulations and a 10mA or 30mA residual Current Device (RCD) must be fitted to the mains supply. Consult a qualified electrician or local authority if in any doubt about wiring to the mains supply. Always unplug or disconnect ALL electrical appliances within the pond from the electricity supply before placing your hands in the water.

WARNING: OPERATIONAL USE. Do not use the electrical cord to lift the pump as this may cause damage. We recommend fitting a lifting cord when the pump is installed in deep water. These pumps are not suitable for water temperatures above 35 degree C. Do not allow the pump to freeze. Using the pump without the strainer cage being fitted may invalidate the warranty.

PUMP INSTALLATION. These dirty water pumps are for use as waterfall or pond filter pumps only and are not suitable for fountains or in swimming pools. The larger the diameter of hose used the better the flow of water, especially over long runs. When the hose diameter has been selected, cut the unwanted smaller steps from the hose tail, fit the hose and secure with a suitable hose clip.

PUMP MAINTENANCE. A quick daily check should be made to ensure that the pump is running satisfactorily. If the flow of water seems to be reduced remove and clean the strainer cage and check that the impeller is running free. Once a year disassemble the pump including the rotor assembly and wash all components and remove any lime-scale build up.

PUMP TESTING. The FTP Series of pumps have been safety tested according to EN 60335 -1 and 2 and EN 50366 and complies with Directive 2006/95/EC. GS Certificate No: SI50096659

PUMP GUARANTEE. If the pump, excluding the rotor assembly, becomes unserviceable within one year from the date of purchase it will be repaired or replaced at our option free of charge, unless in our opinion the pump has been subject to damage, misuse or a repair has been attempted by an unauthorised person. Liability is not accepted for damage due to accident, improper installation or use. Liability is limited to the replacement of a faulty pump. This guarantee is not transferable and does not affect your statutory rights. If the pump fails please contact the retailer from whom it was purchased.

Manufacturer:	Jebao
Model Number:	FTP
Guarantee Period :	1 Year from date of purchase
Purchase Date:/...../.....

Retailer/Dealer Stamp

When returning products under guarantee please indicate the reason for return and attach proof of purchase.

Distributed in the U.K. by:
 J & M Pond Accessories, Rose Cottage, Glenside North, Pinchbeck, Spalding,
 Lincolnshire. PE11 3SD Tel: 01775 710882