AQUAMAX Eco CLASSIC

The powerful classic in a completely new design



- Uncompromisingly reliable it pumps pond water and course debris particles up to 8mm into the filter
- The entry level series of filter and watercourse pumps from OASE
- Extremely economical: Thanks to its energy-efficient motor, the AquaMax Eco Classic constantly saves electricity and therefore money while in operation
- Suitable for use on swim ponds and bathing ponds (used in an exterior pump chamber)
- Included in the scope of delivery: Special hose adapter with threaded collar for different hose sizes
- »Environmental Function Control« (EFC by OASE) protects against dry run and blocking

AquaMax Eco Classic 2500E / 3500E

• Up to 40% more efficient than previous models

START



Matching filters and filter systems starting on page 34

		AquaMax Eco Classic 2500E	AquaMax Eco Classic 3500E	AquaMax Eco Classic 5500	AquaMax Eco Classic 8500	AquaMax Eco Classic 11500	AquaMax Eco Classic 14500	AquaMax Eco Classic 17500
Dimensions (L x W x H)	mm	280 x 230 x 140						
Rated voltage		220 - 240 V / 50 Hz						
Power consumption	W	23	35	60	80	100	135	170
Guarantee (+ request guarantee) *P. 173	Years	3 + 2						
Max. flow rate	l/h	2600	3500	5300	8300	11000	13600	17400
Max. head height, metres	m	2.20	2.60	2.80	3.20	3.30	3.40	3.70
Hose connection mr	n (inch)	25 / 32 / 38 (1", 1 ¼", 1 ½")						
Filter intake surface	cm²	810						
Max. coarse debris displacement	mm				8			
Setup type		Can be setup underwater & dry installed						
Item no. (GB-Version)		20241	20264	51098	51100	51103	51109	56710
Item no.		20225	20249	51096	51099	51102	51104	56653

